

Output Ratings		
Generating Set Model	P32P1S	P35E1S
220 – 240V, 50 Hz	32 kVA 32 kW	35 kVA 35 kW
240V, 60 Hz	36 kVA 36 kW	40 kVA 40 kW

Ratings at unity pf

Ratings Definitions

Prime Power – Model P32P1S

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P35E1S

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3).

Technical Data

Engine Model:	Perkins 1004G	
Alternator Model:	LL2014H	
Number of Cylinders:	4 in line	
Cubic Capacity: Litres (cu.in)	3.99 (243)	
Bore/Stroke: mm (in)	100 (3.94)/127.0 (5.00)	
Compression ratio:	16.0:1	
Aspiration:	Natural	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	45.0 (60.0)	52.5 (70.5)
BMEP: kPA (psi)	902 (131)	877 (127)
Piston Speed: m/sec (ft/sec)	6.35 (20.8)	7.62 (25.0)
Fuel Tank Capacity: Litres (US Gal)	176 (46.5)	176 (46.5)
Fuel Consump, P32P1S:1/hr (USg/hr)	11.2 (2.9)	13.7 (3.6)
Fuel Consump, P35E1S:1/hr (USg/hr)	12.3 (3.3)	15.8 (4.2)
Heat Rejection to Exhaust System: kW (Btu/min)	34.9 (1986)	43.8 (2493)
Heat Rejection to Cooling System: kW (Btu/min)	37.0 (2106)	39.0 (2220)
Total Radiated Heat: kW (Btu/min)	15.3 (871)	17.9 (1274)
Exhaust Temperature: °C (°F)	680 (1256)	690 (1274)
Radiator Cooling Air Flow: m³/min (cfm)	160 (5650)	194 (5851)
Combustion Air Flow: m³/min (cfm)	2.6 (91.8)	3.15 (111)
Exhaust Gas Flow: m³/min (cfm)	8.0 (283)	9.7 (343)

Note: Standard reference conditions 27 °C (80 °F) Air Inlet Temp, 152.4m (500ft) A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights

Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
2149 (84.6)	752 (29.6)	1341 (52.8)	820 (1808)	840 (1852)

Dry = With Lube Oil Wet = With Lube Oil and Coolant

Generating set pictured may include optional accessories



P32P1S – P35E1S



FG Wilson (Engineering) Ltd
 Old Glenarm Road, Larne, County Antrim BT40 1EJ
 Northern Ireland, United Kingdom
 Tel: +44 (0) 28 2826 1000 Fax: +44 (0) 28 2826 1111
www.FGWilson.com

